

## TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Bleeder plug	8.3	85	74 in.·lbf
Brake booster clevis lock nut	26	265	19
Brake pedal support sub-assy x Brake pedal sub-assy	36.8	375	27
Brake booster x Body	12.7	130	9
Brake pedal support sub-assy x Body	23.6	240	17
Brake master cylinder x Piston stopper bolt	10	102	7
Brake master cylinder x Reservoir	1.8	18.4	15.9 in.·lbf
Brake master cylinder x Brake booster	12.5	127	9
Brake line union nut	15.2	155	11
Wheel nut	103	1,050	76
Cruise control actuator bracket x Body	43	438	32
Front brake cylinder mounting x Steering knuckle	106.8	1,089	79
Front brake cylinder x Front brake cylinder mounting	34.3	350	25
Front disc brake caliper x Flexible hose	29	296	21
Rear drum brake wheel cylinder x Backing plate	10	102	7
Rear disc brake caliper installation bolt	46.6	475	34
Rear disc brake caliper x Flexible hose	29	296	21
Proportioning valve assy x Body	5.4	55	48 in.·lbf
Brake actuator assy x Actuator bracket	4.7	48	42 in.·lbf
Brake actuator bracket x Body	19	194	14
Front speed sensor x Steering knuckle	8.0	82	71 in.·lbf
Front speed sensor wire harness clamp x Shock absorber	29	296	21
Front speed sensor wire harness clamp x Body	8.0	82	71 in.·lbf
Rear speed sensor x Knuckle	8.0	82	71 in.·lbf
Yawrate sensor bracket set bolt	21	214	15
Yawrate sensor x Body	21	214	15