

## TORQUE SPECIFICATION

| Part Tightened  |        | N-m | kgf-cm | ft-lbf     |
|---|--------|-----|--------|------------|
| Fuel delivery pipe sub-assy x Cylinder head sub-assy (1ZZ-FE)     | Bolt A | 19  | 194    | 14         |
|   | Bolt B | 9.0 | 92     | 80 in.-lbf |
| Cylinder head cover No. 2 x Cylinder head cover sub-assy (1ZZ-FE) |        | 7.0 | 71     | 62 in.-lbf |
| Fuel delivery pipe sub-assy x Cylinder head sub-assy (2ZZ-GE)     | Bolt A | 29  | 296    | 21         |
|   | Bolt B | 9.0 | 92     | 80 in.-lbf |
| Clamp x Cylinder head cover sub-assy (2ZZ-GE)                     |        | 9.0 | 92     | 80 in.-lbf |
| Engine wire x Cylinder head cover sub-assy (2ZZ-GE)               |        | 10  | 102    | 7          |
| Fuel tank vent tube set plate x Fuel tank assy                    |        | 6.0 | 61     | 53 in.-lbf |
| Separate type rear seat cushion assy x Body                       |        | 41  | 420    | 30         |
| Fuel tank protector No. 2 x Fuel tank assy (4WD)                  |        | 6.0 | 61     | 53 in.-lbf |
| Fuel tube clamp No. 4 x Fuel tank assy                            |        | 6.0 | 61     | 53 in.-lbf |
| Fuel tank band sub-assy No. 1 x Body                              |        | 39  | 400    | 29         |
| Fuel tank band sub-assy No. 1 LH x Body                           |        | 39  | 400    | 29         |
| Parking brake cable assy No. 2 x Body                             |        | 5.4 | 55     | 48 in.-lbf |
| Parking brake cable assy No. 3 x Body                             |        | 5.4 | 55     | 48 in.-lbf |
| Fuel tank protector No. 1 x Body                                  |        | 5.4 | 55     | 48 in.-lbf |
| Fuel tank protector No. 1 x Fuel tank band sub-assy No. 1         |        | 5.4 | 55     | 48 in.-lbf |
| Exhaust pipe assy front x Exhaust manifold (FF)                   |        | 43  | 440    | 32         |
| Exhaust pipe assy front x Tail pipe assy (FF)                     |        | 43  | 440    | 32         |
| Floor panel brace front x Body (FF)                               |        | 30  | 302    | 22         |
| Fuel tank inlet valve assy x Fuel tank assy (4WD)                 |        | 3.5 | 36     | 31 in.-lbf |
| Fuel tube clamp No. 4 x Fuel tank assy (4WD)                      |        | 6.0 | 61     | 53 in.-lbf |
| Check valve protector x Fuel tank assy (4WD)                      |        | 3.5 | 36     | 53 in.-lbf |
| Evaporation vent tube clamp No. 2 x Fuel tank assy (4WD)          |        | 6.0 | 61     | 53 in.-lbf |
| Charcoal canister assy x Body (4WD)                               |        | 19  | 194    | 14         |
| Front floor heat insulator No. 2 x Body (4WD)                     |        | 5.5 | 56     | 49 in.-lbf |
| Front floor heat insulator No. 1 x Body (4WD)                     |        | 5.5 | 56     | 49 in.-lbf |
| Exhaust pipe assy center x Exhaust pipe assy front (4WD)          |        | 43  | 440    | 32         |
| Exhaust pipe assy center x Tail pipe assy (4WD)                   |        | 32  | 330    | 24         |