

TORQUE SPECIFICATION

| Part Tightened | N-m | kgf-cm | ft-lbf |
|---|-----------|---------------|------------|
| Driven pinion gear nut (w/ SST) | 260 – 355 | 2,647 – 3,616 | 191 – 262 |
| Ring gear x Transfer ring gear mounting case | 77.5 | 790 | 57 |
| Bearing cap set bolt | 63.2 | 644 | 47 |
| Transfer extension housing sub-assy x Transfer case | 25.5 | 260 | 19 |
| Transfer extension housing sub-assy x Transfer dynamic damper | 25.5 | 260 | 19 |
| Breather oil deflector set bolt | 6.5 | 66 | 58 in. lbf |
| Transfer case rear cover No.1 x Transfer case | 18.8 | 200 | 14 |
| Transfer drain plug x Transfer assy | 49 | 500 | 36 |
| Transfer case No.1 plug x Transfer assy | 49 | 500 | 36 |
| Transfer case No.2 plug x Transfer assy | 49 | 500 | 36 |
| Stud bolt x Transfer assy | 39.2 | 400 | 29 |
| Transfer assy set nut | 68.8 | 700 | 51 |
| Transfer assy x Transfer stiffener plate | 34 | 347 | 25 |
| Transfer assy x Engine mounting bracket | 64 | 652 | 47 |